

ROOF LADDER DOUBLE SIDED STEP

ROOF LADDER

- With Aluminium alloy rung, anti-slip tread
- Heavy duty channel section
- Strong alloy rubber faced support bars
- Heavy duty rubber feet for prolonged life
- Fully repairable
- Manufactured with BS EN131 compliant materials

ORDERING CODES	LENGTH	RUNGS PER SECTION	APPROX WEIGHT
GLI2RL	3.5m	12	15kg
GLI9RL	5.5m	19	21kg



Glassfibre - GLRL Range



KM 37107
Kitemarked
BSEN131

Glassfibre - GTS / AFDS Range

DOUBLE SIDED STEP

- Available in both alloy tread and all fibre versions
- Anti-slip tread
- Heavy duty channel section
- Heavy duty rubber feet for prolonged life
- Complies with ANSI 14.5 & ESI 13-1
- Fully repairable
- All items listed here are Kitemarked BS EN131

ORDERING CODES		LENGTH CLOSED	NUMBER OF TREADS	APPROX WEIGHT
ALUMINIUM TREAD	G/FIBRE TREAD			
GTS04	AFDS04	1.07m	4	8.5kg
GTS05	AFDS05	1.32m	5	10.0kg
GTS06	AFDS06	1.58m	6	12.5kg
GTS07	AFDS07	1.83m	7	14.0kg
GTS08	AFDS08	2.09m	8	15.5kg
GTS09	AFDS09	2.34m	9	19.0kg
GTS10	AFDS10	2.59m	10	20.5kg