



Easy-rise Steps with truck/dock platform

48 degree slope for extra safety and comfort

750 x 1200mm platform

Designed to allow user to descend the steps facing forward

Large platform with removable chain on end and both sides for 3-sided access.

Welded steel tube and bar construction.

Fitted with handlock anchorage.

Front feet, fitted with protective plastic floor pads

Expamet treads and large working top platform makes them ideal for loading and unloading items outside.

Wheels: 2 front swivel castors with 100mm dia rubber tyred wheels with roller bearings

2 rear axle-mounted 200mm wheels with rubber tyres and roller bearings.

Finish: All steelwork red epoxy or galvanised finish

Tread width 750 mm.

Platform W x D: 750 x 1200 mm

No. of treads inc platform	Average working height	Platform height mm	Overall H x W x D mm	Red Expamet Ref	wt. kg	Galv Expamet Ref	wt. kg
4	2420 mm	920	1910 x 960 x 1870	S681	89	S691	89
5	2650 mm	1150	2140 x 960 x 2060	S682	98	S692	98
6	2880 mm	1380	2370 x 960 x 2250	S683	107	S693	107

Tilt and Go Steps

Welded steel tube and bar construction. Expamet treads and large working top platform makes them ideal for loading and unloading items outside.

The steps have 2 handles at the front, fitted with knuckle guard hand grips for safe lifting and moving.

Wheels: 2 rear 200mm steel centred wheels with rubber tyres and roller bearings.

Option

Inward opening gate on platform end.

Ref **S700** (Extra).



Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation.

Tread width 500 mm.

Platform W x D: 500 x 600 mm

No. of treads inc platform	Average working height	Platform height mm	Overall H x W x D mm	Blue Expamet Ref	wt. kg	Galvanised Expamet Ref	wt. kg
3	2250 mm	750	1760 x 650 x 1345	S701	36	S711	36
4	2500 mm	1000	2010 x 650 x 1535	S702	41	S712	41
5	2750 mm	1250	2260 x 650 x 1725	S703	46	S713	46
6	3000 mm	1500	2510 x 650 x 1915	S704	51	S714	51



Tilt and Go