

Steptek Quality Red Range

560mm tread width

Hand built with attention to detail, both in design and manufacture, to ensure total reliability and many years of arduous operation.

Welded steel tube and bar construction.

Fitted with hand lock anchorage; when locked the front feet rest firmly on the floor, feet fitted with protective plastic floor pads.

Outboard axle mounted rear wheels gives extra stability.

Finish: All steelwork red epoxy finish.

Wheels: Front 2 swivel castors with 100 mm dia. rubber tyred wheels with roller bearings. Rear 2 axle mounted 200 mm dia. wheels with rubber tyres and roller bearings.

Accessories

Lower gate

Fully welded hinged steel tube gate fitted to bottom of steps (not removable). Gate folds back through 270°. Fitted with padlock facility (padlock not supplied)
Ref **S170** (Extra)



Hook-on tool tray

(capacity 5kg) L x W x D: 600 x 250 x 220 mm
Ref **S089** (Extra)

Hook-on wire basket

(capacity 5kg) L x W x D: 600 x 250 x 220 mm
Ref **S088** (Extra)



Model S162

Platform gate option



Inward opening spring loaded platform gate, with spring loaded plunger bolt, to fit at the end, or either side of the top platform. The gate closes against a vertical retention plate. Option adds to length of platform and o/a length:
5-9 tread +380mm
10-14 tread +300mm
Ref **S175** (Extra)

A caution notice is fitted to each set to remind user of operation procedure.


A health and safety at work information sheet is supplied.



Hand lock anchorage; when locked the front feet rest firmly on the floor

Tread width 560 mm. Platform W x D: 5-9 steps 560 x 380 mm; 10-14 steps 560 x 460 mm

Tread choices



No. of treads inc platform	Average working height	Platform height mm	Overall H x W x D mm	Ribbed rubber treads		Punched treads		Anti-slip treads		Aluminium treads	
				Ref	wt.	Ref	wt.	Ref	wt.	Ref	wt.
5	2750 mm	1250	2165 x 850 x 1220	S130	53	S140	51	S150	53	S160	54
6	3000 mm	1500	2415 x 850 x 1400	S131	58	S141	56	S151	58	S161	60
7	3250 mm	1750	2665 x 850 x 1580	S132	63	S142	61	S152	63	S162	65
8	3500 mm	2000	2915 x 850 x 1760	S133	70	S143	68	S153	70	S163	73
9	3750 mm	2250	3165 x 850 x 1940	S134	76	S144	73	S154	76	S164	78
10	4000 mm	2500	3415 x 1000 x 2200	S135	89	S145	85	S155	89	S165	92
11	4250 mm	2750	3665 x 1000 x 2380	S136	98	S146	94	S156	98	S166	101
12	4500 mm	3000	3915 x 1000 x 2560	S137	110	S147	106	S157	110	S167	113
13	4750 mm	3250	4165 x 1250 x 2740	S138	117	S148	112	S158	117	S168	121
14	5000 mm	3500	4415 x 1250 x 2920	S139	124	S149	120	S159	124	S169	127
15 - 20	Please ask for details										