

Antistatic workbenches

Static control cantilever workstations with conductive or static dissipative worksurfaces

Worktop options:

(BFB) Black fibreboard worksurface

Conductive resistance to ground:

1x 10⁻³ - 1x 10⁻⁵ ohms

(ALA) Grey laminate worksurface

Static dissipative resistance to ground:

1x 10⁻⁴ - 9x 10⁻⁶ ohms



Medium duty (300kg) construction
14 & 16swg to BS6323.

Cantilever leg design, fitted with
4 adjustable feet.



Colours

Frames finished in light grey epoxy.

Cupboard and drawer carcass finished in

Light Grey epoxy.

Drawer fronts and doors available in:

Blue

Red

or Dark Grey

Blue supplied if none specified.

Workbenches

c/w earth grounding cord + press stud

length x Depth mm	Worktop		
	BFB	ALA	
1200	600	AS1-BFB	AS1-ALA
	750	AS2-BFB	AS2-ALA
	900	AS3-BFB	AS3-ALA
1500	600	AS4-BFB	AS4-ALA
	750	AS5-BFB	AS5-ALA
	900	AS6-BFB	AS6-ALA
1800	600	AS7-BFB	AS7-ALA
	750	AS8-BFB	AS8-ALA
	900	AS9-BFB	AS9-ALA

Accessories - above bench

Accessory	Ref	Posts reqd
-----------	-----	------------

Extension posts (pair)

required for the following accessories

Short

SES-A

Tall

TES-A

Top light frame

with 1200mm flourescent fitting and diffuser

1200	TLF4-A	TES
1500	TLF5-A	TES
1800	TLF6-A	TES

Top shelf - steel

290mm depth

1200	TSS4-A	TES
1500	TSS5-A	TES
1800	TSS6-A	TES

Top shelf - Dissipative laminate

290mm depth

1200	TDL4-A	TES
1500	TDL5-A	TES
1800	TDL6-A	TES

Rear louvre panel

450mm high

1200	RLP4-A	SES
1500	RLP5-A	SES
1800	RLP6-A	SES

Rear service duct

2 x 13amp sockets and insulators

1200	RSD4-A	-
1500	RSD5-A	-
1800	RSD6-A	-

Accessories - below bench

Accessory H x W x D	Left fitted	Right fitted
------------------------	----------------	-----------------

Single drawer

140 x 410 x 430mm	LA	RA
-------------------	----	----

2 drawer unit

280 x 410 x 430mm	LE	RE
-------------------	----	----

3 drawer unit

420 x 410 x 430mm	LH	RH
-------------------	----	----

4 drawer unit

560 x 410 x 430mm	LK	RK
-------------------	----	----

small cupboard

420 x 410 x 430mm	LC	RC
-------------------	----	----

Single drawer + small cupboard

560 x 410 x 430mm	LG	RG
-------------------	----	----

Large cupboard

560 x 410 x 430mm	LD	RD
-------------------	----	----

Timber workbenches

Timber workbenches are recommended for use in industrial, commercial, educational training centres and home workshops



Timber workbenches

Height x Depth 840 x 750mm

Worktop	Plywood	Vinyl	Hardwood
L: 1200mm	T426P	T426V	T426H
L: 1500mm	T526P	T526V	T526H
L: 1800mm	T626P	T626V	T626H

Robust timber construction

Choice of worktops

Standard depth: 750mm
Standard working height 840mm
(900mm available on request).

Finish: Clear varnish

Worktops

Plywood: 36mm plywood with wood edge
Vinyl: 2.5mm vinyl bonded to 36mm MDF with wood edge
Hardwood: 44mm hardwood

Construction

Legs: 85 x 65mm
Upper side rails: 144 x 25mm
Lower side rails: 88 x 28mm
Lower shelf: 18mm plywood

Additional antistatic equipment

ADT002

ADT004

ADT005

ADT006

ADT020

ADT001

ADT003

ADT009

ADT010

ADT024

ADT022

Antistatic equipment	
Accessory	Ref
General	
Earth bonding plug	ADT001
Wristband and cord	ADT002
Wriststrap connection point	ADT003
Straight cord	ADT004
Earth lead and plug	ADT005
Heel grounder	ADT006
Testers	
Wristband tester	ADT009
Resistivity tester	ADT010
Matting	
Bench mat with stud	ADT011
1200 x 600mm	
Floor mat with stud	ADT012
1200 x 1500mm	
Seating (medistat vinyl)	
Standard conductive chair	ADT024
Ergonomic conductive chair	ADT022
Arms (pair)	ADT023
Sign	
Warning sign (rigid plastic)	ADT020